



2MP CAMERA

GE-HFW-1220-SP



GE-HFW-1220-SP



Shop No. 338/1, G.M. Complex, Ganthipuram Sixth St,
Gandipuram, Coimbatore, Tamil Nadu 641012



+0 98433 59251



nidhienterprisesbbe@gmail.com
www.grandeye.net

Introduction

GE-HFW-1220-SP The camera is suitable for the scenes which requires high definition image display such as finance, telecommunications, government, schools, shops, airports, factories and hotels and so on.

Specification

Model		GE-HFW-1220-SP
Application Scene	Image Sensor	1/2.9inch CMOS
	Resolution	2M
	Image Size	1920x1080
	Video Output	AHD/TVI/CVI/CVBS
	Image System	PAL/NTSC920×1080/1280×1024/1024×768
	Electronic Shutter	TVI/CVI/AHD:1080P Lite,720P, WD1 real time
	IR Distance	10-20m
	Frame Rate	30FPS(60Hz) 25FPS(50Hz)
	Min. Illumination	0lux IR ON
	Lens	3.6 mm
	Lens Mount	M12
	S / N Ratio	≥52dB AGC OFF
	Ingress Protection	IP54
Functions	Function Control	OSD (COC Control)
	Day & Night	ICR
	Digital WDR	Yes
	Digital NR	Yes
	AGC	Yes
	Auto White Balance	Yes
	BLC	Yes
	Front Light Compensation	Yes
	Defog	No
	HLC	No
	Sharpness	Yes
	Mirror	Yes
	Smart IR	Yes
	Image Setting	Auto
	Language	Chinese / English
Defect Correction	Yes	
Angle Adjustment Case	Any angle	
Others	Power Supply	DC12V(±10%)
	Power Consumption	Day : <65 mA ; Night : <240 mA
	Working Environment	-20 °C , ~ 50 °C , 10% ~ 90% humidity
	Dimensions (mm)	71mm×71mm×156mm

Characteristics

- ❖ 1080P real time image, high resolution, true color84CH DVR support
- ❖ 4 kinds of standard and lossless high-definition video outputs8 / 16
- ❖ Up to 1000 TVL resolution
- ❖ CMOS progressive scan, perfectly capture the moving object16 CH
- ❖ Support OSD menu
- ❖ High speed, long distance, real time transmission
- ❖ Auto color to B / W at low illuminationstyle operation by mouse
- ❖ Support ICR switch, true day / night
- ❖ Support noise reduction function
- ❖ 10-20m IR night view distance
- ❖ IP66 Metal body and weatherproff
- ❖ Support COC
- ❖ Support 960H CVBS output
- ❖ Powerful smart phone & Pad surveillance with iOS and Andriod OS

Dimensions

