

2MP H.265 DVR

GE-XVR 5116-DS4



GE-XVR 5116-DS4

Introduction

GE-XVR 5116-DS4 series are 16 CH 1080P lite high definition DVRs with ability to connect analog and IP cameras simultaneously, which adopt the standard H.264 high profile compression format and the most advanced SOC technique to ensure real time recording in each channel and realize



























4K	Output
	-

HD IPC

STD

Network

Audio

Mohile

Mouse

Ŀ-	m	ıa	Ιl

оасрас	TIDII C	DDNS	310	NELWOIK	1 12			
Specification								
N	Model		GE	E-XVR 5116-DS4				
	Main Processor Chip	Standard	H.265					
System	OS	Embedde	d Linux					
	Coding	Standard H.264 High Profile						
Video	Local Video Input	BNC×16						
	Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280						
	Input Resolution	TVI/CVI/AHD:1080P Lite,720P, WD1 real time CVBS						
	Network Input/	IPC×1 / 6Mbps						
Audio	Local Audio Input	RCA×1						
	2-way Audio	Take up c	hannel one aud	lio input				
	Local Output	RCA×1						
Record	Record Stream		am recording					
	Resolution	5MP / 4MP / 3MP / 1080P / 960P / 720P						
	Mode	Manual, timer, motion, sensor						
	Bit Stream	768Kbps-	-4Mbps					
	Image Quality	5 Level						
	Resolution	1080P/960	0P/720P					
IPC Input	IPC Record Frame Rate	25fps(PAL	_)/30fps(NTSC)					
Playback	Playback	16 CH	16 CH					
Network	Interface	RJ45 10 / 100 Mbps × 1						
	Network Protocol	TCP / IP, P	PPPoE, DHCP, D	NS, DDNS, UPnP, NT	P, SMTP GB28181			
Storage	HDD	SATA×4						
Storage	Maximum Capacity of HDD	6T						
Dardona	USB Backup	Yes						
Backup	eSata Backup	No						
	Alarm Input	No						
Interface	Alarm Output	No						
	Communication	No						
	Remote	Optional						
	USB	USB2.0×2	(in the rear pan	el)				
	Computer Case	mini 1Upa	anel)					
Others	Dimensionr	255×223×	42 W×D×H					
	Power Supply	DC12V						
	Power Comsuption	≤ 5W (wit	thout HDD)					
	Work Environment	-10 ~ 50 °C	C ,10% ~ 90% h	umidity				

Characteristics

- ★ 16 CH TVI / CVI / AHD video input CVBS
- ❖ 16 CH DVR support 1080P lite / 720P / WD1 recording
- ♣ 18 / 16 CH DVRs support 1080P lite / 720P / 720P lite / WD1 recording
- ♣ 4/8 CH DVRs support 1/1 CH IPC 1080P/960P/720P recording
- 16 CH DVRs support 2 CH IPC 3MP / 1080P / 960P / 720P recording
- ❖ Adopt standard H.264 high profile compression format to get highquality video at much lower bit rate
- . Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback: 4 / 8 / 16 CH simultaneously playback
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP,DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- ❖ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log review and device status review
- HDMI 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

Dimensions \odot \odot \odot \odot \odot Rear Panel for 16CH