

5MP H.265 DVR

GE-XVR 5532-DS4



GE-XVR 5532-DS4



Introduction

GE-XVR 5532-DS4 series are 5MP high definition hybrid DVRs with ability to connect analog and IP cameras simultaneously, which adopt the standard H.264 high profile compression format and the most advanced SOC technique to ensure real time recording in each channel and realize outstanding



























4K Output

HD IPC

DDNS

STD

Networ

etwork

PTZ

Audio

MIC

Мо

Mobile

CI

CMS

IISR

Mouse

E-mail

4K Output	HD IPC	DDNS	STD	Network	PTZ
Specification					
Model		GE-XVR 5532-DS4			
System	Main Processor Chip	Cortex A9			
	OS	Embedde	d Linux		
	Coding	Standard	H.264 High Prof	ile	
Video	Local Video Input	BNC×32			
	Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280			
	Input Resolution	TVI/CVI/AI	HD:1080P Lite,7	20P, WD1 real time C	CVBS
	Network Input/	IPC×1/6Mbps			
Audio	Local Audio Input	RCA×1 / R	CAx4		
	2-way Audio	Take up c	hannel one aud	io input	
	Local Output	RCA×1			
Record	Record Stream		m recording		
	Resolution		P / 3MP / 1080P		
	Mode		imer, motion, se	ensor	
	Bit Stream	768Kbps-	4Mbps		
	Image Quality	5 Level			
IPC Input	Resolution	1080P/960	DP/720P		
	IPC Record Frame Rate	25fps(PAL	.)/30fps(NTSC)		
Playback	Playback	32 CH			
Network	Interface	RJ45 10 /	100 Mbps × 1		
	Network Protocol		PPoE, DHCP, DN	IS, DDNS, UPnP, NTI	P, SMTP GB28181
Storage	HDD	SATA×4			
	Maximum Capacity of HDD	6T			
Backup	USB Backup	Yes			
	eSata Backup	No			
Interface	Alarm Input	No			
	Alarm Output	No			
	Communication	No			
	Remote	Optional			
	USB	USB2.0×2	(in the rear pan	el)	
Others	Computer Case	mini 1Upa	nel)		
	Dimensionr	255×223×	42 W×D×H		
	Power Supply	DC12V			
	Power Comsuption	≤10W (w	ithout HDD)		
	Work Environment	-10 ~ 50 °C	.10% ~ 90% h	umidity	

Characteristics

- 32 CH TVI / CVI / AHD video input CVBS
- 32 CH DVR support 1080P lite / 720P / WD1 recording
- № 18 / 16 CH DVRs support 1080P lite / 720P / 720P lite / WD1 recording
- ♣ 4/8 CH DVRs support 1/1 CH IPC 1080P/960P/720P recording
- ◆ 16 CH DVRs support 2 CH IPC 3MP / 1080P / 960P / 720P recording
- Adopt standard H.264 high profile compression format to get highquality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback: 4 / 8 / 16 CH simultaneously playback
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP,DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- ... Authorization management, log review and device status review
- * HDMI 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

Dimensions OCO ON MUBIC VIDEO IN OUT CVBS VOA HITM LAN USB DC12V R848